

| VELOTAXI | |
|--|---|
| Frame | Robust tubular steel frame, hand-welded |
| VELOTAXI Cabin | Seating for 2 Persons with rain/sun/wind cover and trunk/luggage compartment (back) |
| Electric Engine | Pedelec 48 Volt 250-Watt BLDC engine + swappable 1152 Wh LiFePo4 battery with Bluetooth interface |
| Drive Train System | SHIMANO Nexus 8-Speed |
| Suspension Fork | Solid, CARGO-optimized double shock absorbers (motorcycle components) |
| Breaking System | Hydraulic disc brakes (at each wheel) |
| Suspension | Spring damper units for extra comfort |
| Wheels & Tires | 17" Aluminium rims and heavy-duty tires |
| Lighting | LED Headlight + 2 x Taillights (LED) |
| Paint Scheme | Impact resistant powder coating |
| Weight/Max. Total Weight* | 175 kg / max. 500 kg |
| Dimensions (LxWxH)* | 294 cm x 109.5 cm x 195 cm |
| VELOTAXI Cabin/Trunk Dimensions (LxWxH)* | Seating for 2 Persons / 27 cm x 109.5 cm x 195 cm |
| Standard Features | • Reverse gear, solid 25mm rear axle with uni-mass springs, luggage compartment (back), mudguards, parking brakes |
| Optional Features | • Engine variants: VALEO, BOSCH, BAFANG etc. • Replacement LiFePo4 battery (Standard: 1152 Wh) or customized battery variants • Paint finish in RAL colors, customized branding, foil coating and/or LED Paneling • Rearview mirror, Rain/Sun Cover • SUPREME DUTCH Airless Tires • SCHWALBE PICKUP E-CARGO Tires 20" • ALLIGT CARGO-Wheels (CBW5 Hybrid) |

* State of Planning 04/2024: All dimensions and weights are approximate figures which are based on prototypes and may differ in serial production. In addition, they depend on customer's specific system configuration as optional features might have a changing effect.

